



## **MICROBE-LIFT® Technology Eliminates the Need for Capital Investment at a Rendering Plant in Guatemala**

**Location:** ARECA’s Frisa Rendering Plant, Palin, Guatemala

**Background:** The facility is a rendering plant, utilizing a limited waste water system. The basic design has a cooling tower, from which the water passes through a grease trap and then into an aeration tower. The water is then discharged into a series of three small lagoons, with a retention time that is calculated to be between 10 and 15 days based on a system volume of 110,000 gallons in the tanks and lagoons and the flow which was believed to vary between 6,857 and 11,428 gallons per day.

**Objective:** This plant contacted the technical representative at **Ecological Laboratories Inc.** to determine if bioaugmentation could lower the effluent COD to avoid the need to expand their system. The local regulations had targeted a 50% reduction by 2014 and an additional 50% reduction by 2024 for every facility in the river basin.

After thorough evaluation of their system, **Ecological Laboratories Inc.** developed a treatment plan using **MICROBE-LIFT®/IND** as follows:

Location	Volume Gallons	Week #1 Gal/week	Weeks #2-4 Gal/week	Maintenance Gal/week
Aerator #1	10 m <sup>3</sup>	2	1	½
Lagoon #1	120 m <sup>3</sup>	2	1	½
Lagoon #2	120 m <sup>3</sup>	1	½	½
Lagoon #3	120 m <sup>3</sup>	1	½	½
Total	370 m <sup>3</sup>	6	3	2

**Results Achieved:** From the initial application of **MICROBE-LIFT®/IND**, the effluent COD was reduced by 74% while the effluent BOD was reduced by 86%. (See chart below)

Parameter	Influent	Effluent (April 1)	Effluent (June 6)
COD mg/l	6,290	1,420	363
BOD mg/l	5,700	1,140	164
Improvement		74%	86%

Based on the first 5 weeks of the plan, treatment with **MICROBE-LIFT®/IND** was able to meet the 2024 goals without any further capital investment, while eliminating odor.

# MICROBE-LIFT® Technology Eliminates the Need for Capital Investment at a Rendering Plant



**Fig. 1:** These pictures taken on 5/22/09 (above) and 7/1/09 (below) show the condition of the three lagoons after treatment compared to during treatment. Note the condition of the lagoons improve from the first to the third lagoon in the series.

**Ecological Laboratories, Inc.** also recommended that by constructing a simple block wall one meter high to increase the lagoon depths, they could increase the retention time to provide an anticipated effluent discharge below 100 mg/l COD and 50 mg/l BOD.

For more information on **MICROBE-LIFT®** Technology contact  
**Ecological Laboratories Inc.**  
[www.EcologicalLabs.com](http://www.EcologicalLabs.com)  
CS14303